

BUCKET ELEVATOR

MODEL: BL-150/200/250/300/350/400



STANDARD CONSTRUCTION:

- Height of elevator is option, standard is 8.0 meter high
- A number of leg sections plus a head and boot piece with pipe connections between these.
- One of the leg sections with access for belt mounting and safety belt cover.
- Elevator head with motor drive bracket.
- Elevator boot with adjustment device for belt tensioning and cleanout door on both sides.
- Plexiglass window for visual inspection.
- Butterfly valve to adjust the flow direction is option
- And elevator buckets.
- Pulleys for V-belt of motor or chain sprocket of gear motor are option.
- Complete set bucket elevator except spout pipes and spare parts

Note: head and boot pieces are delivered assembled; body connections between these are delivered in pieces.

DIMENSIONS OF ELEVATOR

Model	Intake Capacity (T/hr)	Required power (kW)	Belt speed (m/s)	Outside dimensions			Weight (kg)
				LxWxH (mm)			
BL-150	1-2	0.75	2	250	150	8,000	-
BL-200	3-6	1.1	2	440	200	8,000	-
BL-250	6-10	2.2	1.95	580	250	8,000	-
BL-300	10-15	2.2	1.85	650	300	8,000	-
BL-350	15-25	4.0	1.75	800	400	8,000	-
BL-400	30-40	5.5	1.75	1,000	500	8,000	-

N.P.T GROUP NHAN PHONG THAI CO., LTD.

161/28/21 Binh Tri Dong Street, Binh Tan District, HCMC.

Tel: + 08 54072938 Fax: + 08 62601256

Email: sales@npt-group.com